

## GEARIN' UP



### BBE SOUND TWO TIMER

The BBE Two Timer lets the user employ two delay times, footswitchable via the Time 1/Time2 mode switch. The Two Timer circuit features 1-percent metal film resistors, true hardwire bypass, a delay range of 0-330ms, repeat and mix functions, plus on/off LED indicator. See it at [bbsound.com](http://bbsound.com).



### BARGE CONCEPTS PEDALS

Barge Concepts Dual Boost DB-3 is a linear pre-amplifier with two channels, each with its own controls for Gain and Volume, and an effects loop between the two channels. The Barge GLZ-1 Gain Signal Buffer is a low-noise, true-bypass, opamp-based signal buffer with 0-15 dB clean boost buffered volume control (L control), and variable impedance control (Z control). For more, visit [bargeconcepts.com](http://bargeconcepts.com).



### ELIXIR CABLES

Elixir Cables are available in lengths of 10, 15, 20 and 30 feet with right-angle and/or straight jack plugs. They are designed to remain flexible, with non-twist memory, branded plugs, and custom grip housings. See [elixirstrings.com](http://elixirstrings.com).



### NS DESIGN CR4

The NS Design CR4 Bass Cello offers authentic upright bass tone with a 34" bass guitar scale and standard bass tuning. It uses the NS Polar Pickup System and EMG magnetic pickups. Visit [nedsteinberger.com](http://nedsteinberger.com).

